MVL-HT-05-110

0.5 x 110mm 1/2" TELECENTRIC LENS

HT series Telecentric Lens are designed for machine vision application with excellent imaging quality, magnification range from 0.5x to 2.0x, working distance range from 65mm to 150mm, optional point light interface.

Key Features

- High resolution and uniformity of image definition
- Low optical distortion and high telecentricity, more suitable for high precision measurement application
- Excellent anti-vibration performance and stability performance in temperature variation
- Image size compatible with 1/1.8"








	MVL-HT-05-110						
Parameter	0.5x 110mm 1/2" TELECENTRIC LENS						
Magnification		0.5x		Working Distance		110±2mm	
Depth of Field*		3mm		Resolution		12.61μm	
Optical Distortion		≤ 0.1%		Telecentricity		≤ 0.1°	
F-Number		F9.4		Object Space NA		0.027	
Image Size		Ф8.4mm		Object-image Distance		227.43 ± 2mm	
Mount		C-Mount		Dimension		99.9mm×30mm	
Operating Temperature		-10~50°C		Weight		84g	
Field of View (mm)	D	1/3"	12	1/2"	16	1/1.8"	17.8
	Н		9.6		12.8		14.4
	V		7.2		9.6		10.6

^{*}The Depth of Field is the theoretical calculated value when the diameter of the maximum confusion circle is 40µm.

Dimension



Germany, Austria, Switzerland

Sedeco Imaging GmbH Unterer Dammweg 12 76149 Karlsruhe Germany T. +49 721 5604 7980 info@sedeco-imaging.com BeNeLux Sedeco Imaging B.V. Trasmolenlaan 12 3447 GZ Woerden the Netherlands T, +31 348 749110 info@sedeco-imaging.nl

vww.sedeco-imaging.com

Hangzhou Hikrobot Technology Co.,Ltd.

No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.

en.hikrobotics.com